

EUROPEAN WINDOW SYSTEMS

2400 TILT & TURN

Other Products

<u>Product By Operation</u>	2 11/16" Tilt & Turn	2 1/2" Tilt & Turn
<u>Model</u>	2400 (E) (XE)	
<u>Frame Depth</u> Benefit: Increased structural performance	2 11/16"	2 1/2"
<u>Assembly</u> Benefit: Increased strength & rigidity both frame and vent, vent will not rack	Corner Gussets Both Frame & Vent	Corner Gussets Frame only
<u>Flange Frame Option</u>	13/16"	Not Available most others
<u>Curtain Wall Frame Option</u> Benefit: Minimized sightline, easier transition & increased weather resistance	Yes	No
<u>Frame Depth Alternates</u> Benefit: Flexibility with increased structural demand & esthetics	3 11/16" (E), 4 1/2" (XE)	None
<u>101/I.S. 2-97 Rating</u>	DA-AW90	DA-AW50 to 70
<u>AAMA Test Size</u>	60" x 99"	60" x 99"
<u>Standard Colors</u> Benefit: Countless color options	180 + RAL Colors	8 standard colors
<u>Mfr Size On W&H</u> Benefit: tighter tolerances	to the 1/16"	to the 1/8"
<u>Stnd. Glazing</u> Benefit: Increased thermal & acoustic performance standard	1 1/4" IG (3/16" Min Glass thickness With Low-E)	1" IG (1/8" min without Low-E)
<u>Optional Glazing</u> Benefit: Availability of increased thermal & acoustic performance	IG up to 1 7/8" Dual w/ Blinds	IG up to 1 1/4" Unavailable

Optional finishes: Anodizing and interior wood cladding
Accessories available: panning, expander, receptor & subsill
1271 Boston corner Rd, Millerton, NY 12546

EUROPEAN WINDOW SYSTEMS

2420 TURN IN ONLY

Other Products

<u>Product By Operation</u>	2 11/16" Turn in only	2 1/2" Inswing Casement
<u>Model</u>	2420 (E) (XE)	
<u>Frame Depth</u>	2 11/16"	2 1/2"
Benefit: Increased structural performance		
<u>Assembly</u>	Corner Gussets Both Frame & Vent	Corner Gussets Frame only
Benefit: Increased strength & rigidity both frame and vent, vent will not rack		
<u>Flange Frame Option</u>	13/16"	Up to 2 1/2"
<u>Curtain Wall Frame Option</u>	Yes	No
Benefit: Minimized sightline, easier transition & increased weather resistance		
<u>Frame Depth Alternates</u>	3 11/16" (E), 4 1/2" (XE)	None
Benefit: Flexibility with increased structural demand & esthetics		
<u>101/I.S. 2-97 Rating</u>	DA-AW90	C-AW100
<u>AAMA Test Size</u>	60" x 99"	36" x 60"
Benefit: Larger window sizes		
<u>Standard Colors</u>	180+ RAL Colors	8 standard colors
Benefit: Countless color options		
<u>Mfr Size On W&H</u>	to the 1/16"	to the 1/8"
Benefit: tighter tolerances		
<u>Std. Glazing</u>	1 1/4" IG (3/16" Min Glass thickness With Low-E)	1" IG (1/8" min without Low-E)
Benefit: Increased thermal & acoustic performance standard		
<u>Optional Glazing</u>	IG up to 1 7/8" Dual w/ Blinds	IG up to 1 1/4" Unavailable
Benefit: Availability of increased thermal & acoustic performance		

Optional finishes: Anodizing and interior wood cladding
Accessories available: panning, expander, receptor & subsill
1271 Boston corner Rd, Millerton, NY 12546

EUROPEAN WINDOW SYSTEMS

2430 TILT IN ONLY

Other Products

<u>Product By Operation</u>	2 11/16" Tilt in only	2 1/2" Project In
<u>Model</u>	2430 (E) (XE)	
<u>Frame Depth</u> Benefit: Increased structural performance	2 11/16"	2 1/2"
<u>Assembly</u> Benefit: Increased strength & rigidity both frame and vent, vent will not rack	Corner Gussets Both Frame & Vent	Corner Gussets Frame only
<u>Flange Frame Option</u>	13/16"	Up to 2 1/2"
<u>Curtain Wall Frame Option</u> Benefit: Minimized sightline, easier transition & increased weather resistance	Yes	No
<u>Frame Depth Alternates</u> Benefit: Flexibility with increased structural demand & esthetics	3 11/16" (E), 4 1/2" (XE)	None
<u>101/I.S. 2-97 Rating</u>	DA-AW90	AP-AW100
<u>AAMA Test Size</u> Benefit: Larger window sizes	60" x 99"	60" x 36"
<u>Standard Colors</u> Benefit: Countless color options	180+ RAL Colors	8 standard colors
<u>Mfr Size On W&H</u> Benefit: tighter tolerances	to the 1/16"	to the 1/8"
<u>Std. Glazing</u> Benefit: Increased thermal & acoustic performance standard	1 1/4" IG (3/16" Min Glass thickness With Low-E)	1" IG (1/8" min without Low-E)
<u>Optional Glazing</u> Benefit: Availability of increased thermal & acoustic performance	IG up to 1 7/8" Dual w/ Blinds	IG up to 1 1/4" Unavailable

Optional finishes: Anodizing and interior wood cladding
Accessories available: panning, expander, receptor & subsill
1271 Boston corner Rd, Millerton, NY 12546

EUROPEAN WINDOW SYSTEMS

2480 BALCONY DOOR

Other Products

<u>Product By Operation</u>	2 11/16" Balcony Door	2 1/2" Terrace Door
<u>Model</u>	2480 (E) (XE)	
<u>Frame Depth</u> Benefit: Increased structural performance	2 11/16"	2 1/2"
<u>Assembly</u> Benefit: Increased strength & rigidity both frame and vent, vent will not rack	Corner Gussets Both Frame & Vent	Corner Gussets Frame only
<u>Flange Frame Option</u>	13/16"	Up to 2 1/2"
<u>Curtain Wall Frame Option</u> Benefit: Minimized sightline, easier transition & increased weather resistance	Yes	No
<u>Frame Depth Alternates</u> Benefit: Flexibility with increased structural demand & esthetics	3 11/16" (E), 4 1/2" (XE)	None
<u>101/I.S. 2-97 Rating</u>	DA-AW90	HGD-HC40 to 65
<u>AAMA Test Size</u> Benefit: Life cycle testing on a door	60" x 99"	60" x 97"
<u>Standard Colors</u> Benefit: Countless color options	180+ RAL Colors	8 standard colors
<u>Mfr Size On W&H</u> Benefit: tighter tolerances	to the 1/16"	to the 1/8"
<u>Std. Glazing</u> Benefit: Increased thermal & acoustic performance standard	1 1/4" IG (3/16" Min Glass thickness With Low-E)	1" IG (1/8" min without Low-E)
<u>Optional Glazing</u> Benefit: Availability of increased thermal & acoustic performance	IG up to 1 7/8" Dual w/ Blinds	IG up to 1 1/4" Unavailable

Optional finishes: Anodizing and interior wood cladding
Accessories available: panning, expander, receptor & subsill
1271 Boston corner Rd, Millerton, NY 12546

EUROPEAN WINDOW SYSTEMS

2410 FIXED

Other Products

<u>Product By Operation</u>	2 11/16" Balcony Door	2 1/2" Fixed
<u>Model</u>	2410 (E) (XE)	
<u>Frame Depth</u> Benefit: Increased structural performance	2 11/16"	2 1/2"
<u>Assembly</u> Benefit: Increased strength & rigidity both frame and vent, vent will not rack	Corner Gussets	Corner Gussets
<u>Flange Frame Option</u>	13/16"	Up to 2 1/2"
<u>Curtain Wall Frame Option</u> Benefit: Minimized sightline, easier transition & increased weather resistance	Yes	No
<u>Frame Depth Alternates</u> Benefit: Flexibility with increased structural demand & esthetics	3 11/16" (E), 4 1/2" (XE)	None
<u>101/I.S. 2-97 Rating</u>	DA-AW80	HGD-AW100
<u>AAMA Test Size</u> Benefit: Life cycle testing on a door	60" x 99"	60" x 96"
<u>Standard Colors</u> Benefit: Countless color options	180+ RAL Colors	8 standard colors
<u>Mfr Size On W&H</u> Benefit: tighter tolerances	to the 1/16"	to the 1/8"
<u>Std. Glazing</u> Benefit: Increased thermal & acoustic performance standard	1 1/4" IG (3/16" Min Glass thickness With Low-E)	1" IG (1/8" min without Low-E)
<u>Optional Glazing</u> Benefit: Availability of increased thermal & acoustic performance	IG up to 1 7/8" Dual w/ Blinds	IG up to 1 1/4" Unavailable

Optional finishes: Anodizing and interior wood cladding
Accessories available: panning, expander, receptor & subsill
1271 Boston corner Rd, Millerton, NY 12546